

STONE XL RIGICORE CLICK 5.5

CONSTRUCTION / CONSTRUCTION / COSTRUZIONE / CONSTRUCTIE / KONSTRUKTION	STONE XL RIGICORE CLICK 5.5
TOTAL THICKNESS / EPAISSEUR TOTALE / SPESSORE / TOTALE DIKTE / TOTAL DICKE	4.0 MM RIGICORE + 1.5 MM IXPE
WEAR LAYER / COUCHE D'USURE / STRATO D'USURA / SLEJTLAAG / NUTZSCHICHT	 5.5 MM
UTILIZATION CLASS / CLASSE D'USAGE / CLASSE D'UTILIZZO / GEBRUIKERSKLASSE / STRAPAZIERKLASSE	 CLASS 34
COATING / PROTECTION / RIVESTIMENTO / BESCHERMING / BESCHICHTUNG	ANTISCRATCH PU-GUARD
EMBOSSING / STRUCTURE / STRUTTURA / STRUCTUUR / STRUKTUR	CONCRETE
BEVELLED / BISEAUTÉ / BISELLATURA / V-GROEF / ABGESCHRÄGT	YES
PLANK SIZE / DIMENSIONS DE LA LAME / DIMENSIONI / AFMETING PER PANEEL / ABMESSUNG DER DIELEN	 465 X 760 MM
CARTON PACKING / EMBALLAGES EN CARTON / SCATOLE / KARTONNEN VERPAKKING / KARTONVERPACKUNG	2.12 M ² 6 TILES
PALLET PACKING / BOÎTES PAR PALETTE / NR SCATOLE À PALETTE / DOZEN PER PALLET / VERPACKUNG AUF PALETTE	50 PACKS / 875 KG / PALLET
IMPACT SOUND REDUCTION / RÉDUCTION DU BRUIT D'IMPACT / RIDUZIONE DEL RUMORE DA CALPESTIO / IMPACT GELUIDVERMINDERING / AUSWIRKUNG KLANG REDUKTION	EN ISO 717-2 22 dB
CASTOR CHAIR RESISTANCE / ESSAI DE LA CHAISE À ROULETTES / PROVA CON POLTRONA A ROTELLE / ROLWEERSTAND BUREAUStOEL / STUHLROLLENWIDERSTAND	EN ISO 4918 - EN 425  PASS
MICRO-SCRATCH RESISTANCE / RÉSISTANCE AUX MICRO-RAYURES / RESISTENZA AI MICRO-GRAFFI / MICRO-KRASBESTENDIGHEID / MIKROKRATZWIDERSTAND	EN 16094 ≥ MSR-B2
ELECTROSTATIC PERFORMANCE / POTENTIEL DE CHARGE ELECTROSTATIQUE / POTENZIALE DI CARICA ELETTROSTATICA / ELECTROSTATISCHE EIGENSCHAPPEN / ELEKTROSTATISCHE EIGENSCHAFT	EN 1815  < 2 KV
SLIP RESISTANCE / ANTIDÉPARANT / RESISTENZA ALLO SCIVOLAMENTO / SLIPWEERSTAND / RUTSCHFESTIGKEIT	DIN 51130  RIO
WEAR RESISTANCE / RÉSISTANCE D'USURE / RESISTANCE ALL'USURA / SLEJTVASTHEID / VERSCHLEISSBESTÄNDIGKEIT	EN 660-2  GROUP T
RESIDUAL INDENTATION / POINÇONNEMENT RÉMANENT / SENSIBILITÀ DI IMPRESSIONE / INDRUKGEVOELIHEID / RESTEINDRUCK	EN ISO 24343-1  PASS
DIMENSIONAL STABILITY / STABILITÉ DIMENSIONELLE / STABILITÀ DIMENSIONALE / DIMENSIONALE STABILITEIT / DIMENSIONSSTABILITÄT	EN 434  ≤ 0.05%
FIRE RATING / CLASSIFICATION AU FEU / CLASSIFICAZIONE AL FUOCO / BRANDKLASSE / BRANDKLASSE	EN ISO 9239-1  BFL-S1
FORMALDEHYDE EMISSION / EMISSION DE FORMALDEHYDE / EMISSIONE DI FORMALDEIDE / FORMALDEHYDE EMISSIE / FORMALDEHYD-EMISSION	EN717-1  CLASS E1
WARRANTY FOR DOMESTIC USE / PÉRIODE DE GARANTIE USAGE DOMESTIQUE / GARANZIA PER USO DOMESTICO / GARANTIEPERIODE HUISHOUELIJK GEBRUIK / GARANTIE FÜR PRIVATEGEBRAUCH	25 YEARS
WARRANTY FOR COMMERCIAL USE / PÉRIODE DE GARANTIE USAGE COMMERCIAL / GARANZIA PER USO COMMERCIALE / GARANTIEPERIODE COMMERCIEEL GEBRUIK / GARANTIE FÜR KOMMERZIELLEN GEBRAUCH	10 YEARS